AUTOFLO

WALL MOUNT AA2-B

ENGINEERED TO BE BETTER

MAINS POWER SENSOR TAP - WALL MOUNTED

The Australian designed and manufactured, **Autoflo Wall Mount AA2-B** Mains Power Sensor Tap is suitable for hand-washing applications, particularly in the food service, hospitality and health industries where a reliable and affordable hands free sensor tap is of paramount importance for prevention of cross-contamination, hygiene and water saving.

The **Autoflo Wall Mount AA2-MH** is a built for purpose product, with clever features incorporated. The electronics are designed so the water flow is set to run for a period after the hands are removed from the sensor area, as is required in hospitals. The stainless steel sensor plate can simply be mounted to the wall using silicone. Adjustable sensor range and run-time ensure consistent performance in demanding environments.

FEATURES

- Sensor range adjustable
- Run-time adjustment after hands are removed from sensor area
- Elegant chrome straight spout
- Stainless steel sensor plate
- Sensor operation indicator LED
- Power Pack operation indicator LED
- Removable solenoid filter basket
- Simple installation

Order Code: 100-0178

TYPICAL DIMENSIONS

100

186

75

116

WATER RATING
www.waterrating.gov.au
7.0 litres per minute
In accordance with AS/NZS 6400
licence No. 1886
Autoflo Pty Ltd

AUSTRALIAN MADE

AS/NZS 3718
WM 22306

Every effort is made to ensure specifications are correct at the time of printing. Autoflo Pty Ltd reserves the right to make changes without prior notice. All measurements shown are in millimetres.

WWW.AUTOFLO.COM.AU

AUTOFLO

WALL MOUNT AA2-B

ENGINEERED TO BE BETTER

MAINS POWER SENSOR TAP - WALL MOUNTED

TECHNICAL SPECIFICATIONS

- SENSOR TYPE - Active Infrared
- SENSOR RANGE - 180mm factory set
- OPERATING SUPPLY - 24v AC Power Pack
- OPERATING PRESSURE - 50 to 500kPa
- RUN TIME - Max 15 seconds after hands removed
- FLOW RATING - 7 litres per minute
- SOLENOID - 24V
- MAX TEMPERATURE - 50°C

TYPICAL INSTALLATION

Under no circumstances should the solenoid be directly mounted to the spout.

In situations where water pressure to solenoid exceeds 500kPa a pressure limiting valve must be installed. (not supplied)

PRESSURE LIMITING VALVE 500kPa

HOT STOP TAP   COLD STOP TAP

H   C

TEMPERING VALVE

COMPONENTS SUPPLIED

	Item Code	Description
1	300-0190	Wall mount Spout - straight
2	300-0185	Wall mount sensor
3	300-0183	24V AC Solenoid Valve
4	300-0124	24V Power Pack
5	300-3026	Sensor mounting kit

Autoflo Pty Ltd
www.autoflo.com.au

DESIGNED AND MANUFACTURED IN AUSTRALIA TO WORLD STANDARD